


Technical requirement

- 1.Chain ultimate tensile strength is not less than 50kN.
- 2.Under the usual conditions the measuring force is 500N, the measuring number of links is 31,and the measured length shall be 1283.4(+3.2,0).
- 3.Push-off force of pin is not less than 2500N,and push-off force of bush is not less than 1800N.
- 4.Under the usual conditions,the twist angle is less than 4°/m.
- 5.The chain joint shall be turned freely.
- 6.Chain shall be washed and cleaned before packing,marking,packing ,transportion and reserving shall be meet the customer's requirement.



6	CA555-00-05	Roller	48	35	11.6	556.8	
5	CA555-00-03	Inner Plate	48	40Mn	22.1	1060.8	
4	CA555-00-02	Pin	48	20CrMnMo	9.39	450.72	
3	CA555-00-04	Bush	48	20Mn	8.29	397.92	
2	CA555-C6E-00-01	Outer Plate	32	40Mn	24.95	798.4	
1	CA555-C6E-00-01(A)	Outer Att.	8	40Mn	143.02	1144.16	
No.	Item	Description	QTY	Material	Unit Weight	Total Weight	Note
				CA555-C6E Agricultural Chain			
				Assembling Drawing			
				Weight	Ratio	CA555-C6E.6L-00(48L)	
				4.4kg/pc	1:1.6		
Date		2016.10.24					

FIRST DRAFT

REGISTRY TRACER

CHECKER

OLD DRAFT

SIGN

DATE